

## NEW PRODUCT PREVIEW

# PLEATED CARTRIDGES FOR CFLV SERIES FILTERS

## SINGLE AND MULTIPLE CARTRIDGES

### KEY FEATURES AND BENEFITS

- Multiple Micron Ratings for High Efficiency Filtration
- For use with Single (7" diameter) and Multiple (2-1/2" diameter) Cartridge CFLVs (Single and Double Length)
- High Surface Area Design Provides Excellent Flow Rates and Comprehensive Service Life
- Low Pressure Drop
- Multiple Layered Media Construction Guarantees Dependable Performance
- Thermally Bonded DOE End-Caps, Core and Filter Media

### TYPICAL APPLICATIONS

- Water and Wastewater Treatment
- Desalinization, RO and Deionized Water Systems
- Chemical Processing
- Food and Beverage
- Aquatic and Animal Life Support Systems
- Metal Finishing and Plating
- Marine and Corrosive Environments

### MATERIALS



- PP Media
- Cellulose Media
- Plastisol PVC
- PP Core
- ABS Core

### OPERATING CHARACTERISTICS

- Max.  $\Delta P$ : 60 PSI at maximum recommended temperature of 140°F
- Change out recommended at 30 PSID



### SINGLE AND MULTIPLE CARTRIDGE VIEWS



# PLEATED CARTRIDGES FOR CFLV SERIES FILTERS

SINGLE AND MULTIPLE CARTRIDGES



## CFLV SERIES FILTER CARTRIDGES SINGLE (1), FOUR IN CARTON/HAYWARD - PROPRIETARY

NOMINAL MICRON RATING	DESCRIPTION	FILTRATION AREA PER CARTRIDGE sq ft	USE WITH CFLV SERIES ADAPTER KIT
1, 5, 10 and 30	7" x 16" (DOE)* PP Cartridge** For Single Length Series Cartridge Filter	45	CFLVKIT716
1, 5, 10 and 30	7" x 16" (DOE)* PP Double Stacked Cartridge** For Double Length Series Cartridge Filter	45 x 2	CFLVKIT732
1, 5, 10 and 30	7" x 30" (DOE)* PP Cartridge For Double Length Series Cartridge Filter	85	CFLVKIT730



## CFLV SERIES FILTER CARTRIDGES SINGLE (1), FOUR IN CARTON/HAYWARD - PROPRIETARY

NOMINAL MICRON RATING	DESCRIPTION	FILTRATION AREA PER CARTRIDGE sq ft	USE WITH CFLV SERIES ADAPTER KIT
5	7" x 16" (DOE)* Polyester Cellulose Cartridge** For Single Length Series Cartridge Filter	45	CFLVKIT716
5	7" x 16" (DOE)* Polyester Cellulose Double Stacked Cartridge** For Double Length Series Cartridge Filter	45 x 2	CFLVKIT732



## CFLV SERIES FILTER CARTRIDGES - MULTIPLE (5), 25 IN CARTON

NOMINAL MICRON RATING	DESCRIPTION	FILTRATION AREA PER CARTRIDGE sq ft	USE WITH CFLV SERIES ADAPTER KIT
1, 5, 10 and 30	2-1/2" x 10" (DOE)* PP Cartridge** For Single Length Series Cartridge Filter	4.5	MFLVKIT210
1, 5, 10 and 30	2-1/2" x 20" (DOE)* PP Cartridge** For FLT120 or FLT220	9	N/A
1, 5, 10 and 30	2-1/2" x 30" (DOE)* PP Cartridge** For Double Length Series Cartridge Filter	13.5	MFLVKIT230

### NOTES:

\* All end caps are Platisol PVC.

\*\* For chemical compatibility, refer to the Hayward Engineering Product Guide (EPG113) or consult factory. For other media and micron ratings, please consult factory.



Hayward is a registered trademark of Hayward Industries, Inc.  
© 2013 Hayward Industries, Inc.

NPP0713